DF-SA187 – RV Exterior Quick Connect Sprayer with Coiled Hose

MAINTENANCE AND CLEANING

Cleaning Tips: The finish on your product is designed to retain its beautiful sheen for years. To maintain the original look of the finish, a little care and caution should be used. We recommend the use of mild soap and water to clean the product.

THE USE OF ABRASIVE CLEANERS MAY SCRATCH THE FINISH OR CAUSE OTHER DAMAGE.

RECOMMENDED TOOLS AND MATERIALS

- No tools necessary for this installation

BEFORE YOU BEGIN

There are a variety of things to do before installing any new plumbing system into your RV. Before you begin work make sure you:

- Shut off the main water supply
- Cover your drain to prevent loss of parts
- Observed any local plumbing codes
- Inspect fixture for damage - Replace as necessary

* Dura Faucet reserves the right to make any revisions in the design of products without notice.

INSTALLATION

1 Insert Sprayer into Diverter

the sprayer’s hose connection securely into the water diverter.

2 Turn on Water Supplies and Check for Leaks

Once installation of the hose into the diverter is complete, turn the water supply on and allow water to run for at least 30 to 60 seconds each. While water is running, check for leaks at both the diverter and the sprayer head. Everything look good? Great. Now you can start enjoying your new Dura Faucet product!