



DURA FAUCET®

DF-SA400K - RV Hand Held Shower Wand and Hose Kit



MAINTENANCE AND CLEANING

Cleaning Tips: The finish on your product is designed to retain its beautiful sheen for years. To maintain the original look of the finish, a little care and caution should be used. We recommend the use of mild soap and water to clean the product.

THE USE OF ABRASIVE CLEANERS MAY SCRATCH THE FINISH OR CAUSE OTHER DAMAGE.

RECOMMENDED TOOLS AND MATERIALS

- ◆ Adjustable Wrench
- ◆ Plumber's Tape

BEFORE YOU BEGIN

There are a variety of things to do before installing any new plumbing system into your RV. Before you begin work make sure you:

- ◆ Shut off the main water supply
- ◆ Cover your drain to prevent loss of parts
- ◆ Observed any local plumbing codes
- ◆ Inspect fixture for damage - Replace as necessary

* Dura Faucet reserves the right to make any revisions in the design of products without notice.

INSTALLATION

1 Install Mounting Bracket

First, find desired location for mounting bracket and screw on bracket by hand while making sure that the connection for the shower hose is facing down.

2 Install Shower Ring

Find desired location for shower ring at the height that is most comfortable for showering and screw on by hand.

3 Install Handheld Shower Head

Screw on new handheld shower head onto shower hose by turning clockwise onto the hose's threading until taut. An adjustable wrench can be used to tighten onto hose.

4 Turn on Water Supply

Once installed, turn the water on and check for leaks around diverter and threaded connections of the shower hose and hand held shower head. Turn the hot and cold water on for 30 to 60 seconds to remove any potential debris. You can now enjoy your Dura Faucet Hand Held Shower Head.

SPEC DRAWING / PARTS

