

PRODUCT DATA SHEET



ProFlex® RV Rubberized Silicone Roof Coating White

ProFlex® RV Rubberized Silicone White Roof Coating is a premium silicone rubber roof ideal for ponding water.

- Silicone, Metal, aged TPO, PVC and EPDM.
- EPDM rubber roofs must be rinsed with Geocel® Bond-It designed for EPDM roofs. An adhesion peel test must be performed to ensure proper adhesion prior to application. Other roof substrates including TPO, PVC, metal may require primer before application. All single ply such as TPO, PVC and EPDM must be aged to ensure proper adhesion.

Adheres To:

Silicone, Metal, aged TPO, PVC and EPDM.

Part #	Color	Size	Qty/Cs	UPC	SCC
KSRV44300-16	Clear	1 gal	4	050926005238	10050926005235

Composition and Materials:

Silicone

Grade:

Self-leveling, brushable grade consistency

Primer:

An adhesion peel test must be performed to ensure proper adhesion prior to application.

Disclaimer:

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of Geocel® Coatings- A Business Unit of the Sherwin-Williams Company. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of the publication. Consult your ProFlex® Technical Representative to obtain the most recent Product Data Information.

KEEP PRODUCT FROM FREEZING

Installation:

Surface Preparation: For maximum adhesion to heavily oiled or dirty surfaces, areas to be sealed may need to be wiped with a solvent and allowed to dry. Use of a dry rag or brush to remove dust, dirt, or other contaminants is recommended. Contact Geocel Products Group's Technical Service Department or representative if such agents are involved.

LimitedWarranty:

Cleaning:

Virgin Mineral Spirits or Naptha

Cautions:

CONTAINS AROMATIC HYDROCARBONS. Contents are COMBUSTIBLE. Keep away from heat and open flame. VAPOR HARMFUL. Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NOISH approved) or leave the area. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. First Aid: In case of eye contact, flush thoroughly with large amounts of water for 15 minutes and get medical attention. For skin contact, wash thoroughly with soap and water. In case of respiratory difficulty, provide fresh air and call physician. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. **DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE.** Contains solvents which can cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. **Warning:** This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm. **DO NOT TAKE INTERNALLY. KEEP OUT OF REACH OF CHILDREN**

Availability and Cost:

Cost and further technical data are available from your local Geocel Products Group

If when applied according to label directions this product fails to perform in accordance with its published literature, If upon satisfactory evidence of product failure, and as your sole remedy, we will either replace the product at no cost or refund the original purchase price for that portion of product that fails to perform in accordance with this limited warranty. Labor or costs associated with labor are not included. **THIS LIMITED WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY, WHICH ARE ALL DISCLAIMED AND/OR LIMITED IN DURATION TO THE EXTENT PERMITTED BY LAW. WE SHALL NOT BE LIABLE FOR INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES (INCLUDING LOST PROFITS) FROM ANY CAUSE WHATSOEVER AND SUCH DAMAGES ARE EXPRESSLY EXCLUDED.** Some states do not allow the exclusion or limitation of incidental or consequential damages or how long an implied warranty lasts, so the above limitation or exclusion may not apply to you. This limited warranty gives you specific legal rights, and you may also have other rights which vary from state to state.

Typical Physical Properties		
Property	Results	Test Method
Vehicle Base	Silicone	
Tensile at Peak (psi)	275	ASTM D 624
Elongation at Break (%)	425	ASTM D 624
Tack Free Time	4-6 hours	
Viscosity	7,098 cps	ASTM D 562

Technical Services:

Geocel Products Group representatives throughout the U.S. are available to provide technical assistance. Our in-house technical staff and laboratory facilities are equipped to respond to specific requests for further information.



© Geocel

For additional product information, refer to the product spec sheet located at GeocelUSA.com

Geocel Products Group, Cleveland, OH 44115
Phone: (800) 348-7615 Fax: (800) 348-7009