



ProFlex® RV Hybrid Repair Sealant

ProFlex® RV Hybrid Roof Repair Sealant is a premium flashing grade, UV stable sealant that is flexible. It is a durable, weather resistant seal that provides excellent adhesion to a variety of RV substrates. ProFlex® RV Hybrid can be used as seam sealer when applied in accordance with the conditions and application instructions below. Available in White or Gray colors.

Basic Uses:

- Adheres to EPDM, aged TPO, PVC, metal, acrylic coatings and most silicones. A pull test is recommended prior to application for all substrates.
- General uses include perimeter sealing, through-roof projections, termination points, flashings, fasteners, side and end laps of metal building panels, scrim edges, seams, etc. Must be topcoated with silicone or acrylic elastomeric roof coating. Can NOT be topcoated with solvent-based roof coatings. Minimum application @ 60 mils wet film thickness (WFT).
- In areas where water collection or ponding water occurs, ProFlex® silicone topcoat is required.

Adheres To:

EPDM, aged TPO, PVC, metal, acrylic coatings and most silicones.

Part #	Color	Size	Qty/Cs	UPC	SCC
KSRV66320-01	Gray	11oz	6	050926005276	10050926005273
KSRV66321-01	White	11oz	6	050926005283	10050926005280

PRODUCT DATA SHEET

Composition and Materials

Hybrid

Grade:

Self-leveling, brushable grade consistency

Primer:

A pull test is recommended prior to application for all substrates.

Disclaimer:

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of Geocel® Coatings- A Business Unit of the Sherwin-Williams Company. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of the publication. Consult your ProFlex® Technical Representative to obtain the most recent Product Data Information.

If further information is needed, contact ProFlex® Technical Service at 1-888-321-3539.

KEEP PRODUCT FROM FREEZING

Installation:

For best results, remove dust, dirt and contaminants. Surfaces should be clean and dry. GENERAL INSTALLATION AND TOOLING PROCEDURE: Cut tip of nozzle and insert in caulking gun, squeeze trigger to start flow of sealant and apply with steady pressure. Smooth sealant with knife, spatula or chip brush ensuring good contact between the sealant and the substrate. Tooling time: 4-8 minutes.

Cleaning:

100% Virgin Mineral Spirits

Cautions:

CONTAINS AROMATIC HYDROCARBONS. Contents are COMBUSTIBLE. Keep away from heat and open flame. VAPOR HARMFUL. Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NOISH approved) or leave the area. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. First Aid: In case of eye contact, flush thoroughly with large amounts of water for 15 minutes and get medical attention. For skin contact, wash thoroughly with soap and water. In case of respiratory difficulty, provide fresh air and call physician. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Contains solvents which can cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal
Warning: This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm. DO NOT TAKE INTERNALLY. KEEP OUT OF REACH OF CHILDREN

Availability and Cost:

Available from various RV distributors. Cost and further technical data are available from your local Geocel Products Group

Limited Warranty:

ProFlex® and The Sherwin-Williams Company warrants ProFlex® RV Hybrid Roof Repair Sealant to be free from defects in materials and manufacturing. Under this warranty, we will provide, at no charge, a quantity of ProFlex® RV Hybrid Roof Repair Sealant sufficient to replace any ProFlex® RV Hybrid Roof Repair Sealant that is proven to be defective when applied according to our written instructions and in applications recommended by us as suitable for the product. THIS WARRANTY IS THE BUYER'S SOLE AND EXCLUSIVE REMEDY AGAINST PROFLEX® AND THE SHERWIN-WILLIAMS COMPANY REGARDING THE PRODUCT. IN NO EVENT SHALL PROFLEX® OR THE SHERWIN-WILLIAMS COMPANY BE LIABLE FOR ANY CONSEQUENTIAL, SPECIAL, INCIDENTAL, INDIRECT, PUNITIVE OR OTHER DAMAGES ARISING FROM THE USE OR PERFORMANCE OF THE PRODUCT. Since methods of application and on-site conditions can affect performance, PROFLEX® AND THE SHERWIN-WILLIAMS COMPANY MAKE NO OTHER WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE REGARDING THE PRODUCT, AND PROFLEX® AND THE SHERWIN-WILLIAMS COMPANY HEREBY DISCLAIM ALL SUCH OTHER WARRANTIES. DISCLAIMER

Technical Services:

Geocel Products Group representatives throughout the U.S. are available to provide technical assistance. Our in-house technical staff and laboratory facilities are equipped to respond to specific requests for further information.

Typical Physical Properties

Property	Results	Test Method
Vehicle Base	Hybrid	
Tensile at Peak (psi)	115	ASTM D 412
Elongation at Break (%)	732	ASTM D 412
Skin Time	30-60 Minutes	
Viscosity	72 (Brookfield)	